

LEC-Starterkit MINI

LEC-Starterkit with LEC-BASE MINI Standard or Custom, including SD card and ATX power supply (without LEC module and cooling solution)

Features

- SMARC 1.1 compliant carrier board with MXM3 connector
- SD card and USB stick
- ATX power supply, US power cord, EU power cord
- Optional LVDS display



Specifications

Items

- SMARC 1.1 compliant LEC-BASE MINI Standard or Custom carrier board (see extra data sheet for features)
- SD card, 4GB SDHC Card (Class 10)
- USB stick (8GB USB2.0 flash drive)
- ATX power supply, 300W
- US power cord 10A, 125V
- EU power cord 220V
- 7" LCD TFT LVDS display and cables (optional)

Separate Mandatory Order Items Modules

LEC-iMX6, LEC-BT, LEC-BTS, LEC-BW

Heat Spreaders

Heat spreader for LEC-iMX6, LEC-BT, LEC-BTS, LEC-BW

Software

BSP depending on operating system

Ordering Information

- LEC-BASE MINI Standard
 LEC-Starterkit with LEC-BASE MINI Standard, including SD card and power supply (without LEC module and cooling solution)
- LEC-BASE MINI Custom LEC-Starterkit with LEC-BASE MINI Custom, including SD card and power supply (without LEC module and cooling solution)

7" LCD TFT LVDS display and cable (optional)

*other configurations by request



All products and company name listed are trademarks or trade names of their respective companies. Updated Mar. 25, 2019. ©2019 ADLINK Technology, Inc. All Rights Reserved. All specifications are subject to change without further notice.

www.adlinktech.com